




NAŚWIETLACZE LED / LED FLOODLIGHTS

LED MHNC 10W PREMIUM



- projektor oświetleniowy z mikrofalowym czujnikiem ruchu o trzech zakresach regulacji: czas działania, natężenie światła i zasięg detekcji,
- regulacja za pomocą pilota,
- czas działania: 10 sek, 30 sek, 1 min, 5 min, 8 min, 10 min,
- natężenie światła: wyłączony lub 1-10 lx, 10-30 lx, 30-70 lx, 70-150 lx,
- zasięg detekcji: max. 10 m oraz do 5 m i do 8 m,
- kąt detekcji: 120 stopni,
- kąt rozsyłu światła: 120 stopni,
- optymalna wysokość do montażu: 1,8 - 2,5 m,
- w skład oprawy wchodzi wbudowane lampy LED klasy A++ - A,
- nie można wymieniać lamp w oprawie.

- lighting projector with microwave motion sensor of three ranges of adjustment: working time, light intensity and detection range,
- adjustment by a remote,
- working time: 10 sec, 30 sec, 1 min, 5 min, 8 min, 10 min,
- light intensity: off or 1-10 lx, 10-30 lx, 30-70 lx, 70-150 lx,
- detection range: max. 10 m and up to 5 m and to 8 m,
- detection angle: 120 degrees,
- beam angle: 120 degrees,
- optimal installation height: 1,8 - 2,5 m,
- fixture includes built-in A++ - A energy class lamps,
- lamps inside are unchangeable.



MODEL	INDEKS	POBÓR MOCY [W]	BARWA ŚWIATŁA	STRUMIEN ŚWIETLNY [lm]	WAGA NETTO [kg]	PAKOWANIE [szt.]	KOD EAN
MODEL	INDEX	POWER [W]	LIGHT COLOR	LUMINOUS FLUX [lm]	NET WEIGHT [kg]	PACKING [pcs.]	BARCODE
LED MHNC 10W CB	KFNLNC10CB2	10	CIEPŁOBIĄŁA WARM WHITE	800	0,30	30	5902201303667
LED MHNC 10W NB	KFNLNC10NB2	10	NEUTRALNA BIAŁA NEUTRAL WHITE	800	0,30	30	5902201303674
LED MHNC 10W ZB	KFNLNC10ZB2	10	ZIMNOBIĄŁA COOL WHITE	800	0,30	30	5902201303681

